

COMPARISON TABLE - Access control

LEGEND ✓ = included (<i>built-in</i>) ■ = optional (<i>on request</i>) - empty space = unavailable	iZero			TARGA 512	TARGA 504
	BOX Full	COLUMN Entry	COLUMN Full		
Built-in OCR sensor	✓	✓	✓	✓	✓
Standard OCR lens Focus (FF=fixed focus; VF=varifocal) - Mount type	3,6 mm FF	3,6/8 mm FF	3,6/8 mm FF	8/16 mm FF	5~55 mm VF
Average reading distance (<i>min - max</i>) NB: distances vary considerably depending on both the size of the plates and the positioning of the camera (front or side)	1,2~3,5mt	1,2~3,5mt/ 1,5~4mt	1,2~3,5mt/ 1,5~4mt	1,5~4mt/ 3~8mt	3~10mt
Additional context sensor	-	-	-	-	■
MicroSD memory for backup and white lists	✓	-	✓	✓	✓
RS232-485 interface	✓	-	✓	✓	✓
Wiegand interface: <ul style="list-style-type: none"> • 64 bit Siemens • 64 bit Honeywell • 64 bit Nedap • 26 bit SHA1 	✓	-	✓	■	■
OSDP interface (Siemens)	-	-	■	■	■
POE+ 802.3at power supply	✓	-	✓	-	■
230 Vac power supply	-	-	■	■	✓
12 Vdc power supply	✓	✓	✓	✓	-

